



SMART AND FLEXIBLE

- Support of RS485, Ethernet and WiFi communication
- Support of energy meter, meteo station, sensors and other equipment



CONVENIENT O&M

- Inverter batch parameter settings and firmware updates
- PV-Plant maintenance via remote Web access for optimized OPEX
- Active and reactive power control
- Local monitoring



EASY OPERATION

- Night light for maintenance
- Robust enclosure, easy to install

Type designation	
Communication	
Max. number of devices	30
RS485 interface	3
Ethernet	1 * RJ45, 10 / 100 / 1000 Mbps
Digital input	5, Max. 24 VDC
Analog input	4, support 4 ~ 20 mA or 0~10 VDC
Wireless Communication	
4G communication	LTE (FDD): B1, B3, B5, B8 LTE (TDD): B38, B39, B40, B41 TD-SCDMA: B34, B39 CDMA: BC0 GSM:900MHz / 1800MHz WCDMA:B1, B8
WiFi communication	802.11 b / g / n / ac HT20 / 40 / 80 MHz 2.4GHz / 5GHz
Power Supply	
AC input	100 VAC ~ 300 VAC, 50 / 60 Hz
Power consumption	Typ. 20 W, Max. 30 W
Night light for maintenance	<1 W
Ambient Conditions	
Operating Temperature	-30 °C ~ 60 °C
Storage Temperature	-40 °C ~ 80 °C
Relative air humidity	≤95 % (non-condensing)
Elevation	≤4000 m
Protection class	IP66

COM100D

Mechanical parameters	
Dimensions (W * H * D)	460 mm * 315 mm * 126 mm
Weight	6 kg
Mounting type	Wall mounted, outdoor and indoor
Box material	PC
Cable specification	AC cable: outdoor UV protection cable of 1~1.5 mm ² , outside diameter 13~18mm RS485 cable: outdoor UV protection shielded twisted pair (STP) of 0.75~1.5 mm ² , outside diameter 6~18mm Ethernet: CAT5 cable, outdoor UV protection shielded, outside diameter 6~18mm AI, DI: outdoor UV protection cable of 1~1.5 mm ² , outside diameter 4.5~6mm

Ordering information

COM100D	The COM100D includes Logger1000A, AC adapter, SPD, Air switch, Night light Support of 4G and WiFi wireless communication Apply to China, India, Malaysia
---------	---

